

Intelli UPS Q

Su-Kam

Ek nayi soch

DSP based TRUE ONLINE

DOUBLE CONVERSION VFI TECHNOLOGY



Audit your Power Quality through Power Manager Software



SALIENT FEATURES

- Wide Input Voltage & Frequency Window
- Built-in Galvanic Isolation Transformer
- Auto-self Test on LCD Panel
- Fuzzy Logic Controlled battery charging
- Intelligent Battery Management
- Scalable Runtime
- Cold Start

APPLICATIONS


- Workstations/Servers
- Networking Equipment
- Telecom
- Color Labs
- ATM Machines/POS Systems
- Gold Analyser Machines
- Security Systems
- Textile Industry

1 Phase Input - 1 Phase Output

TECHNICAL SPECIFICATIONS

Type	1 Phase Input - 1 Phase Output					
Series	IntelliQ Online UPS					
Technology	DSP based Double Conversion Online UPS system with true galvanic isolation					
Ratings	1 KVA	2 KVA	3 KVA	5 KVA	7.5 KVA	10 KVA
Model	IQ111K	IQ112K	IQ113K	IQ115K	IQ117.5K	IQ1110K
Capacity	1 KVA	2 KVA	3 KVA	5 KVA	7.5 KVA	10 KVA
INPUT						
No. of Phases	1Phase-3Wire P,N,E					
Voltage Range	170 V - 280 Volts AC					
Input Frequency Range	47 to 53Hz.					
OUTPUT						
Power	700 W	1600 W	2400 W	4000 W	6000 W	8000 W
Load PF Range	0.8 lagging					
Phase	1 Phase -2 Wire (P,N)					
Output Waveform	Pure Sine Wave					
Voltage	230 V +/-1%					
Frequency	50Hz +/-0.1%					
Load Crest Factor	> 3:1					
Output Voltage THD	< =3% on Linear Load					
Loading Capacity	110% for 2 Minutes					
BY-PASS						
Maintenance By-Pass	Available					
BATTERIES						
No. of 12V Batteries	4	15	15	15	16	16
Voltage	48 VDC	180 VDC	180 VDC	180 VDC	192 VDC	192 VDC
Battery Charging current	0.8 Amp to 8 Amp	1 Amp to 10 Amp				
Battery Recommendation	From 7.2 Ah to 200 Ah					
Battery Self Test	Automatic & Manual					
User Interface						
Communication port	RS-232 Server and Client					
Operating System	Windows95/98/NT/2000/XP					
GENERAL						
Indication	LCD pannel					
Alarm	Mains Failure, Battery Low, Over Load Short Circuit					
Protection	Short Circuit , Over Voltage & Under Voltage Protection.					
Cooling	Forced Air Cooling					
UPS Efficiency	> 85%					
Operating Temperature	0-45DegC					
Operating Humidity	95% Condensing					
Monitoring Software	Additional Software available for remote monitoring					
Accoustic Noise	<45 Db at 1 meter					
Protection Class	Ip20					
UPS Weight	32Kg (Without Batteries)	40Kg (Without Batteries)	57.5Kg (Without Batteries)	71.5 Kg (Without Batteries)	93Kg (Without Batteries)	108Kg (Without Batteries)
Dimension (L X W X H)	(490 X 225 x 350)MM	(550 X 350 X 325)MM	(475 X 350 X 610)MM	(475 X 350 X 610)MM	(550 X 350 X 660)MM	(550 X 350 X 660)MM

Specifications are subject to change without prior notice.




3 Phase Input - 1 Phase Output

TECHNICAL SPECIFICATIONS

Type	3 Phase Input – 1 Phase Output			
Series	IntelliQ Online UPS			
Technology	DSP based Double Conversion Online UPS with true Galvanic Isolation			
Ratings	10 KVA	15 KVA	20 KVA	25 KVA
Model	IQ3110K	IQ3115K	IQ3120K	IQ3125K
Capacity	10 KVA	15 KVA	20 KVA	25 KVA
INPUT				
No. of Phases	3 Phase- 4 Wire			
Voltage Range	310 V – 480 Volt AC			
Input Frequency Range	47 - 53 Hz			
OUTPUT				
Power	8000 W	12000 W	16000W	20000 W
Load PF Range	0.8 lagging			
Phase	1 Phase -2 Wire (P,N)			
Output Waveform	Pure Sine Wave			
Voltage	230V ± 1%			
Frequency	50Hz +/-0.1%			
Load Crest Factor	> 3:1			
Output Voltage THD	<=3% on Linear Load			
Loading Capacity	110% for 5 Minutes/ 125% for 1 Min/ 150% for 10 Sec			
BY-PASS				
Capacity	125% continues			
Maintenance By-Pass	Available			
BATTERIES				
No. of 12V Batteries	30			
Voltage	360 V DC			
Battery Charging current	0.8 Amp to 8 Amp			
Battery Recommendation	From 7.2 Ah to 200 Ah			
Battery Self Test	Automatic & Manual			
USER INTERFACE				
Communication port	RS-232 Server and Client			
Operating System	Windows95/98/NT/2000/XP			
GENERAL				
Indication	LCD pannel			
Alarm	Mains Failure, Battery Low, Over Load Short Circuit			
Protection	Short Circuit , Over Voltage & Under Voltage Protection.			
Cooling	Forced Air Cooling			
UPS Efficiency	> 90%			
Operating Temperature	0-45DegC			
Operating Humidity	95% Condensing			
Monitoring Software	Additional Software available for remote monitoring			
Accoustic Noise	<45 Db at 1 meter			
Protection Class	Ip20			
UPS Weight	131 Kg (without Batteries)	156 Kg (without Batteries)	170 Kg (without Batteries)	170 Kg (without Batteries)
Dimension (H X W X D)	450MM X 650MM X 700MM	450MM X 650MM X 700MM	450MM X 700MM 730MM	450MM X 700MM X 730MM

Specifications are subject to change without prior notice.



3 phase input - 3 phase output

TECHNICAL SPECIFICATIONS

Type	3 phase input - 3 phase output									
Series	IntelliQ Online UPS									
Technology	DSP based Double Conversion Online UPS system with True Galvanic Isolation									
Ratings	5 KVA	7.5 KVA	10 KVA	15 KVA	20 KVA	25 KVA	30 KVA	40 KVA	50 KVA	65 KVA
Model	IQ335K	IQ337.5K	IQ3310K	IQ3315K	IQ3320K	IQ3325K	IQ3330K	IQ3340K	IQ3350K	IQ3365K
Capacity	5 KVA	7.5 KVA	10 KVA	15 KVA	20 KVA	25 KVA	30 KVA	40 KVA	50 KVA	65 KVA
INPUT										
No. of Phases	3 Phase – 4 Wire									
Voltage Range	310 V – 480 Volt AC									
Input Frequency Range	47 – 53 Hz									
OUTPUT										
Power	4000 W	6000 W	8000 W	12000 W	16000 W	20000 W	24000 W	32000 W	40000 W	52000 W
Load PF Range	0.8 lagging									
Phase	3 Phase- 4 Wire									
Output Waveform	Pure Sine Wave									
Voltage	400V ± 2% (P-P), 380V & 415V user selection also available									
Frequency	50Hz +/-0.1Hz									
Load Crest Factor	> 3:1									
Output Voltage THD	<=3% on Linear Load									
Loading Capacity	110% for 8 Minutes/ 125% for 1 Min/ 150% for 13 Sec									
BY-PASS										
Capacity	125% continues									
Maintenance By-Pass	Available									
BATTERIES										
No. of 12V Batteries	30									
Voltage	360 V DC									
Battery Charging current	10 Amp									
Battery Recommendation	From 7.2 Ah to 200 Ah									
Battery Self Test	Automatic & Manual									
USER INTERFACE										
Communication port	RS-232 Server and Client									
Operating System	Windows95/98/NT/2000/XP									
GENERAL										
Indication	LCD pannel									
Alarm	Mains Failure, Battery Low, Over Load Short Circuit									
Protection	Short Circuit , Over Voltage & Under Voltage Protection.									
Cooling	Forced Air Cooling									
UPS Efficiency	> 90%									
Operating Temperature	0-45DegC									
Operating Humidity	95% Condensing									
Monitoring Software	Additional Software available for remote monitoring									
Accoustic Noise	<45 Db at 1 meter									
Protection Class	Ip20									
UPS Weight (Without Batteries)	105Kg	125Kg	155Kg	198Kg	210Kg	223Kg	240Kg	423.5Kg	500Kg	582Kg
Dimension (L x W x H) (In mm)	(450x700 x700)	(450 x 700 x 700)	(450 x 700 x 700)	(450 x 700 x 700)	(450 x 750 x 700)	(500 x 800 x 750)	(500 x 800 x 750)	(810 x 755 x 1460)	(810 x 755 x 1460)	(810 x 755 x 1460)



Service & Support:
1800-102-4423

Sales Enquiry:
1800-102-7555



Su-Kam Power Systems Limited
Corporate Office: Plot No. 54, Udyog Vihar, Phase VI,
Sector-37, Gurgaon -122001, Haryana, India
Tel: +91-124-4170500 Fax: +91-124-4038700/1/2
E-mail: info@su-kam.com Website: www.su-kam.com